



Clearance certificate

for conversion of the handlebar / stem combination with a 25,4 mm clamping diameter

Wilhelm Humpert GmbH & Co. KG hereby confirms that for the bicycle categories listed below it has no reservations about the use of the following handlebar/stem combination with "**Safety Level 5**".

➤ **City / trekking / e-bikes** with motorised pedal assistance up to a **speed of 25 km/h** and a maximum **permissible total weight of 160 kg**

The combinations have been sufficiently tested and meet the requirements of the "**DIN EN 15194:2017**" standard. A risk analysis has also been carried out. No hazard is therefore to be expected in connection with use on a bicycle in its original condition. However, the prerequisite for this is that the length of the brake and gear cables and/or lines has not been changed and that the bicycle remains in the prescribed condition.


Handlebars		Stems	
Art. No.	Sales designation	Art. No.	Sales designation
16212101	ergotec „ERGO XS/25,4“ / AL 6061 T6	40125001; 40125101	ergotec „CHARISMA/25,4“ / AL 6061 T6
16198101	ergotec „ERGO S/25,4“ / AL 6061 T6	40126001; 40126101	
16200101	ergotec „ERGO M/25,4“ / AL 6061 T6		
16202101	ergotec „ERGO L/25,4“ / AL 6061 T6	40130001; 40130101	ergotec „HIGH CHARISMA/25,4“ / AL 6061 T6
16227101	ergotec „ERGO XL/25,4“ / AL 6061 T6	40135001; 40135101	
16229101	ergotec „ERGO XXL/25,4“ / AL 6061 T6		
		40272001; 40293001	ergotec „COVER/25,4“ / AL 6061 T6

Please note: the last digit "1" refers to the packaging and is "0" in the case of OEM products.

This certificate must be handed over to the customer after the conversion.

Wilhelm Humpert GmbH & Co. KG


Steve Richter, M.A.
Test engineer - Testcenter


Rolf G. Häcker
Head of Product Development
Member of the Certification
Committee

Valid as an original document with the coloured Humpert header and footer, or as a certified copy.

As a bicycle retailer I hereby confirm that
this copy is a true representation of the original:

Stamp/signature