



Clearance certificate

for conversion of the handlebar / stem combination with a 25,4 mm clamping diameter

Wilhelm Humpert GmbH & Co. KG hereby confirms that for the bicycle categories listed below it has no reservations about the use of the following handlebar/stem combination with "Safety Level 6".

- **Single- and multi-track transportation- and cargo bikes** with motorised pedal assistance up to a **speed of 25 km/h** and a maximum **permissible total weight of 300 kg**

The combinations have been sufficiently tested and meet the requirements of the "DIN 79010:2020" standard. A risk analysis has also been carried out. No hazard is therefore to be expected in connection with use on a bicycle in its original condition. However, the prerequisite for this is that the length of the brake and gear cables and/or lines has not been changed and that the bicycle remains in the prescribed condition.


Handlebar		Stem	
Art. No.	Sales designatio	Art. No.	Sales designation
12414001; 12415001	ergotec „FLAT BAR/25,4 / AL 6061 T6	40241001; 40243001 40245001	ergotec „SWELL 2/25,4 / AL 6061 T6
16741001	ergotec „LOW RISER BAR/25,4 / AL 6061 T6	40525001; 40527001	ergotec „PIKE 2/25,4 / AL 6061 T6
16710001	ergotec „RISER BAR 30/25,4 / AL 6061 T6	40529001; 40531001 40532001; 40533001	
16720001	ergotec „RISER BAR 50/25,4 / AL 6061 T6	40435001; 40437001	ergotec „HIGH PIKE 2/25,4 / AL 6061 T6
16730001	ergotec „RISER BAR 70/25,4 / AL 6061 T6	40539001; 40541001 40542001; 40543001	

Please note: the last digit "1" refers to the packaging and is "0" in the case of OEM products.

This certificate must be handed over to the customer after the conversion.

Wilhelm Humpert GmbH & Co. KG


 Steve Richter, M.A.
 Test engineer - Testcenter


 Rolf G. Häcker
 Head of Product Development
 Member of the Certification
 Committee

Valid as an original document with the coloured Humpert header and footer, or as a certified copy.

As a bicycle retailer I hereby confirm that this copy is a true representation of the original:

Stamp/signature